

CVD CMP PAD CONDITIONER



CVD (Chemical Vapor Deposition) Diamond Coated Pad Conditioner

CVD PAD CONDITIONER is totally different technology as the conventional disks which is using metal bonding technology such as electroplating or brazing. Diamond is coated on the patterned substrate using CVD technology with customized designs for each CMP process.


High Technology of CVD Diamond Conditioner

"Engineered quality control"

- Chemical stability : Zero corrosion & metal contamination
- Excellent disk flatness: Uniform tip size & tip exposure
- Working diamond design : PCR & Wafer removal rate tuning by tip size, number, exposure, shape, etc.
- PCR sustainability : consistent PCR over polishing time (Dia. tip size doesn't be changed during CMP process)

Features

- Various patterns can be arranged CVD diamond coated tips
- Apex of the CVD diamond coated tip is flat face
- Allows to engineer the critical pressure applied to each tip for pad conditioning
- EHWA has a patent on the tip size and number for pad conditioning
- Shape of the apex where contacts with pad has not changed over conditioning time, which result in consistent pad cut rate
- Pad cut rate is constant



Application

Customized product depending on the customer's process conditions (Polished material, Pad, Slurry type, etc).

Application	Oxide CMP	W CMP		Cu CMP	
Slurry / Pad	Ceria / Silica base	Bulk	Barrier	Bulk	Barrier
Close cell pad	●	●	●	●	●
Open pores pad	●	●	●	●	●

EHWA DIAMOND IND. CO. LTD.

HEAD OFF. : 374, Nambu-daero, Osan-si,
Gyeonggi-do, 18145, Korea
Tel : (82-31)370-9000
Fax: (82-31)374-9235

SALES DEPT. , Tel : (82-31)370-0500
Fax: (82-31)370-0605

INTERNET : <http://www.ehwadia.co.kr>
E-MAIL : semi@ehwadia.co.kr





EHWA DIAMOND IND. CO. LTD.

HEAD OFF. : 374, Nambu-daero, Osan-si,
Gyeonggi-do, 18145, Korea
Tel : (82-31)370-9000
Fax: (82-31)374-9235

SALES DEPT. , Tel : (82-31)370-0500
Fax: (82-31)370-0605


INTERNET : <http://www.ehwadia.co.kr>
E-MAIL : semi@ehwadia.co.kr

Product Standards of EHWA CVD CMP Pad Conditioner

Contents	Values
Out diameter	2inch ~ 5inch
Tip sizes	Free over 5 μ m
Tip numbers	Free under 30,000ea/disk
Tip height	Free under 100 μ m (Decision by tip size)

Performance

Conventional diamond disk shows a significant change of PCR and Pad roughness conditioning time, but CVD disk maintains constant PCR and Pad roughness because the shape & size of tip do not change.



Conditioning	Conventional Disk	CVD Disk
Over Conditioning (Initial period)		
Stable Conditioning (Middle period)		
Low Conditioning (End period)		